

DESCRIPTION

The fully shielded PWP4 architectural wall pack adds a simple geometric accent to many commercial architectural styles. It is suitable for venues ranging from retail malls, corporate and medical campuses to industrial parks, transportation centers, and schools or universities. The luminaire is durable die-cast aluminum with horizontal tempered flat glass lens for zero uplight. The wall pack is recommended for mounting heights from 12' to 20' depending on illumination levels and uniformity requirements. Options include 10KV surge protection for regions requiring additional protection to emergency battery backup for normal or cold temperature environments.



Date: _____ Type: _____ Catalog Number: _____

Project Name: _____

ORDERING INFORMATION

| LUMINAIRE | | | | | | |
|---------------------------------|-----------------|---------------|------------------|----------------|------------------------|---|
| MODEL | OUTPUT | CCT | VOLTAGE | OPTIC | FINISH | OPTIONS |
| PWP4 Architectural Wall Pack | 23W 23 Watts | 30K 3000K | UNV 120-277V | T3 Type III | DB Dark Bronze | SF Single Fuse, 120-277V models only |
| | 47W 47 Watts | 40K 4000K | 347V 347-480V | | CC Custom RAL Color | DF Double Fuse, 120-277V models only |
| | | 50K 5000K* | | | | SP Surge Protection - 10KV |
| | | | | | | PC Photocell 120-277VAC |
| | | | | | | EM Emergency Battery Backup 120-277V models only |
| | | | | | | EMC Cold Start Emergency Battery Backup -20°C, 90 Minutes 120-277V models only |

Custom solutions are available; consult factory via phone at (864) 487-3535 ext. 258 or via email at DesignServices@EXP-Brands.com.

DLC Qualified: PWP4-47W-50K-UNV



| PWP4 | | | |
|---------------------|------------------------|--|--|
| PHYSICAL | HOUSING | Die-Cast Aluminum with Full Cutoff Frame | |
| | LENS | Tempered Clear Flat Glass | |
| | HARDWARE | Nickel-Plated Stainless Steel Hardware | |
| | OPERATING TEMPERATURE | -40°F to 104°F | |
| | FINISH | Powder Coat Finish | |
| | MOUNTING HEIGHT | 12 to 20 Feet | |
| ELECTRICAL | POWER | 23 Watts | 47 Watts |
| | CURRENT | 0.19 Amps @ 120 Volts 0.08 Amps @ 277 Volts | 0.39 Amps @ 120 Volts 0.17 Amps @ 277 Volts |
| | VOLTAGE | Universal 120 to 277 Volts or High Voltage 347-480 Volts | |
| | DRIVER | Electronic Internal Driver, Less Than 20% THD Dimming Source Current: 150 Microamps | |
| | SURGE SUPPRESSION | Standard Internal Surge Protection: 6kV | |
| | CONTROL | 0-10v Dimming for a Dimming Range of 100% to 10% | |
| | FREQUENCY | 50/60Hz | |
| | POWER FACTOR | > 0.90 | |
| PHOTOMETRIC | LED | Static White 3000K, 4000K, and 5000K | |
| | OPTICS | Type III Distribution | |
| | DELIVERED LUMEN OUTPUT | up to 4921 Lumens | |
| | EFFICACY | up to 105 Lumens per Watt | |
| | LUMEN MAINTENANCE | L70 > 50,000 Hours at 77°F* | |
| | BUG RATING | B1-U1-G1 | |
| LIGHT DISTRIBUTIONS | CCT | DELIVERED LUMENS | |
| | | 23 Watts | 47 Watts |
| | 3000K | 2228 | 4552 |
| | 4000K | 2318 | 4736 |
| | 5000K | 2408 | 4921 |
| CERTIFICATIONS | SAFETY | ETL Listed for Wet Locations | |
| | INGRESS PROTECTION | IP65 | |
| | WARRANTY | Five-Year Limited Warranty | |

DIMENSIONS

All dimensions are shown in inches.

